

## MINI DIGITAL CLAMP METER

### MS2002/MS2102

#### Features:

- ▶ Jaw Size:  $\Phi 28\text{mm}/1.1''$
- ▶ Tests AC/DC Voltage and Current, Resistance and Continuity
- ▶ Data Hold and Display Back Light



Specifications	MS2002	MS2102
<b>Specifications</b>	<b>Range</b>	<b>Accuracy</b>
DC Voltage	600V 400V/600V	$\pm(1.0\%+2)$ $\pm(1.0\%+2)$
AC Voltage	600V 400V/600V	$\pm(1.5\%+5)$ $\pm(1.5\%+5)$
DC Current	40A/400A	$\pm(2.5\%+3)$
AC Current	2A/20A/200A 40A/400A	$\pm(2.0\%+5)$ $\pm(2.0\%+5)$
Resistance	2000 $\Omega$	$\pm(1.0\%+3)$ $\pm(1.0\%+3)$
<b>Features</b>		
Display	counts	2000      4000
Jaw Opening		$\Phi 28\text{mm}/1.1''$ $\Phi 28\text{mm}/1.1''$
Continuity Buzzer	<50 $\Omega$	●      ●
Data Hold		●      ●
Display Light		●      ●
<b>General</b>		
Power Supply	2x1.5V AAA Batteries	
Product Size	194mmx72mmx35mm/7.63"x2.8"x1.4"	
Product Weight	198g/0.44lb	
Safety Rating	CAT.II 600V	



#### MS2002

**JAW SIZE**

$\Phi 28\text{mm}/1.1''$

**CURRENT**

AC 200A



#### MS2102

**JAW SIZE**

$\Phi 28\text{mm}/1.1''$

**CURRENT** AC 400A  
DC 400A

