

DATA SHEET

CORD6ASFXMSH

4 pairs patch cords RJ45 S/FTP - CAT6A LSZH - LINK+

BENEFITS

- Excellent electromagnetic immunity thanks to S / FTP shielding
- Excellent transmission performance thanks to very low contact resistivity
- Excellent transmission performance: connection on 2 levels to improve the NEXT









DESCRIPTION / APPLICATIONS -

Designed to ensure an appropriate protection level against electromagnetic interference, the S/FTP cable achieves the performance of the Class Ea Channel which extends up to 500MHz.

VOICE: Analog, ISDN, VOIP

DATA: Ethernet 10 Gbit/s

COMPONENTS: CAT6A performances

POWER SUPPLY: Up to 4PPoE

STANDARDS —

COMPONENTS: TIA 563-C.2 CAT6A

ISO 11801 CAT6A

FIRE BEHAVIOR: IEC 60332-1

SYSTEM: ISO/IEC 11801 Ed3 Class Ea

EIA TIA 568-C.2 CAT6A

EN 50173-1/2011 Class Ea







DATA SHEET

PROPERTIES -

OPERATING TEMPERATURE: -20°C / +60°C

MINIMUM BENDING RADIUS: 8 x cable diameter

INSERTION CYCLES: 750 cycles min / 1000 nom

COMPLIANCE: RoHS

ORDERING INFORMATION -

P/N	DESCRIPTION	PACKING
CORD6ASF003xMSH	CAT6A S/FTP RJ45 patch cord 0.30 meter - LSZH - LINK+ range	Unit
CORD6ASF01xMSH	CAT6A S/FTP RJ45 patch cord 1 meter - LSZH - LINK+ range	Unit
CORD6ASF02xMSH	CAT6A S/FTP RJ45 patch cord 2 meters - LSZH - LINK+ range	Unit
CORD6ASF03xMSH	CAT6A S/FTP RJ45 patch cord 3 meters - LSZH - LINK+ range	Unit
CORD6ASF05xMSH	CAT6A S/FTP RJ45 patch cord 5 meters - LSZH - LINK+ range	Unit
CORD6ASF10xMSH	CAT6A S/FTP RJ45 patch cord 10 meters - LSZH - LINK+ range	Unit

Replace x with the desired colour: J: Yellow / B: Blue / R: Red / V: Green

Delete x for grey colour

