

DIGITAL AC CLAMP METER

C-LOGIC 810



- Power Supply : 3×1.5V AAA Batteries
- Display 6000 counts
- Jaw Opening $\Phi 26\text{mm}/1.0''$
- Auto & Manual Ranging
- Auto Power Off
- Non-Contact Voltage Detector
- Diode Open Voltage 3.2V
- Continuity Buzzer $<50\Omega$
- Data Hold
- Display Backlight
- Work Light
- Low Battery Display
- Product Size :
218mm×78mm×35mm/8.9"×3.1"×1.4"
- Product Weight : 239g/0.53lb
- Certificate : RoHS
- Safety Rating : CAT III 600V

C-LOGIC 810

DIGITAL AC CLAMP METER

General	
Power Supply	3x1.5V AAA Batteries
Product Size	218mm×78mm×35mm
Product Weight	239g
Certificate	CE / ETL / RoHS
Safety Rating	CAT III 600V

Specs	
Display Counts	6000
Jaw Opening	Φ26mm/1.0"
Auto Ranging	✓
Auto Power Off	✓
Non-Contact Voltage Detector	✓
Open Voltage	1.5V
Continuity Buzzer	<60Ω
Data Hold	✓
Display Backlight	✓
Work Light	✓
Low Battery Display	✓

C-LOGIC 810

DIGITAL AC CLAMP METER

Specs	Range	Resolution	Accuracy
DC Voltage	600 mV/6/60 V	0,1 mV/0,001/0,01 V	±(0,8%+2)
	600V	1V	±(1%+2)
AC Voltage	600 mV/6/60 V	0,1 mV/0,001/0,01 V	±(1%+10)
	600V	1V	±(1,2%+10)
AC Current	6/60/600 A	0,001/0,01/0,1 A	±(2,5%+10)
Resistance	600 Ω/6/60/600 KΩ/6 MΩ	0,1 Ω/0,001/0,01/0,1/1 KΩ	±(1,2%+2)
	60MΩ	0,01 MΩ	±(2%+2)
Capacitance	10/100/1000 nF	0,001/0,01/0,1 nF	±(3%+10)
	10/100/1000 nF	1/10/100 nF	±(3%+10)
	10/60 mF	10μF	±(4%+10)
Frequency (A)	100 Hz/1 KHz	0,01/0,1 Hz	±(1,5%+5)
Frequency (V)	100 Hz/1/10 KHz	0,01/0,1 Hz/0,001 KHz	±(1,5%+5)
Frequency (Hz/Duty)	10/100 Hz/1/10 KHz	0,001/0,01/0,1 Hz/0,001 KHz	±(0,5%+5)
	100 KHz/1/10 MHz	0,01/0,1 KHz/0,001 MHz	±(0,5%+5)
Duty cycle	0,5-99 %	0,10%	±(1,5%+15)
Temperature	-20-1000 °C	1 °C	±(2%+2)
	-4-1832 °F	1 °F	±(2%+4)

Product Code Information

SKU	CLOGIC810CBINT
EAN code	8435394775616
UPC code	810053671191
Pcs/export carton	20