


## DIGITAL MULTIMETER

# C-LOGIC 5100



- Power supply: 1X9V 6F22 battery
- Show 2000 counts
- Automatic shutdown
- Transistor hFE 0~1000
- Open diode voltage 3.0V
- Continuity buzzer <50Ω
- Data retention
- Low battery display
- Product size: 188mmx93mmx50mm /7.4 "x3.7 "x1.96".
- Product weight : 380g/0.84lb
- Certificate: CE/ ETL / RoHS
- Safety rating: CAT III 600V

### CONTENTS



# C-LOGIC 5100

## DIGITAL MULTIMETER

General	
Power Supply	1x9V 6F22 Battery
Product Size	188mm×93mm×50mm
Product Weight	380g
Certification	CE/ETL/RoHS
Safety Rating	CAT III 600V

Specs	
Display Counts	2000
Auto Power Off	✓
Transistor hFE	0~1000
Open Voltage	3.0V
Continuity Buzzer	<50Ω
Data Hold	✓
Low Battery Display	✓

Specs	Range	Resolution	Accuracy
DC Voltage	200 mV/2/20/200 V	0.1/1/10 mV/0.1V	±(0,5%+2)
	600 v	1 V	±(0,8%+2)
AC Voltage	2/20/200 V	1/10 mV/0.1V	±(0,8%+3)
	600V	1V	±(1,2%+3)

# C-LOGIC 5100

## DIGITAL MULTIMETER

Specs	Range	Resolution	Accuracy
DC Current	2/20 mA	1/10 $\mu$ A	$\pm(0,8\%+1)$
	200 mA	0,1 mA	$\pm(1,5\%+1)$
	10A	0,01A	$\pm(2\%+5)$
AC Current	20 mA	10 $\mu$ A	$\pm(1\%+5)$
	200 mA	0,1 mA	$\pm(1,8\%+5)$
	10A	0,01A	$\pm(3\%+7)$
Resistance	200 $\Omega$	0.1 $\Omega$	$\pm(0,8\%+3)$
	2/20/200 K $\Omega$ /2M $\Omega$	1/10 $\Omega$ /0.1/1 K $\Omega$	$\pm(0,8\%+2)$
	20M $\Omega$	10 K $\Omega$	$\pm(1\%+2)$
	200M $\Omega$	0.1 M $\Omega$	$\pm(6\%+10)$
Frequency	20 KHz	0,01 KHz	$\pm(2\%+5)$
Temperature	-20-0 $^{\circ}$ C	1 $^{\circ}$ C	$\pm(5.0\%+4)$
	1-400 $^{\circ}$ C	1 $^{\circ}$ C	$\pm(2\%+3)$
	401-1000 $^{\circ}$ C	1 $^{\circ}$ C	$\pm(2\%+5)$

### Product Code Information

SKU	CLOGIC5100CBINT
EAN code	8435394775562
UPC code	810053670941
Pcs/export carton	20