











				800	117	
0		<u></u>		490	<u> </u>	
	78.5				117	
-		ļ	-	450		
		Rail &	Cable	mana	agemen	t slot

IEC60297-2 DIN41494;PART1; DIN41494;PART7 Material: rails and rails mounting accessories the zinc - coated steel sheets other SPCC cold rolled steel; 19" rails and 19" rails mounting accessories, Caster Support plate: 2.0mm, Top Bar 1.5mm,Door, Top panel, Side frame 1.2mm, others: 1.0mm Loading Capacity: Static loading: 1300KG

Comply with ANSI/EIA RS-310-D.

Compliance:

Model	D	Н	Α	Е
595002	1000	2000	911	476

- Packaging: VE cabinets could be shipped in disassembled packing, saving transportation and storage cost.
- New appearance design :Side door: split into 2 parts, lockable with square locks.
 Front and rear door: pluggable front door and rear doors, with external hinges.

 Casters: built-in installation design.
- 3. Frame: duplex profile frames with patent, could be connected by 8 pieces of screws.

 4. Front and rear doors: 'two points' locking design
- making doors and frames closed tighter, turning angle up to 180 degrees.
- Cable entries on top and bottom: sliding and adjustable cable entries on top and bottom, edges of cable entries are with the design to prevent wires from scratching.
- 6. Fan unit: installed from top outside of cabinet, easy to install and maintain.
- 7. Mounting rails: installation positions of mounting rails could be adjusted quickly. Dedicated channel alignment reserved in internal of cabinets.
- 8. Cabinet structure: patented structure.
- 9. Maximum loading capacity: 1300kg