





SPECIFICATIONS

		Input voltage	LAMP		LED		Mounting Hole
			Voltage	Power Consumption	Voltage	Power Consumption	
	KH-501	110VAC	6.3VAC	1.0W	-	-	ø25
	KH-501L		-	-	6V	40mA	
	KH-501TL	6.3V, 12V, 24V	6.3V, 12V, 24V	1.0W	-	-	ø25
	KH-502	220VAC	6.3VAC	1.0W	-	-	ø25
	KH-502L		-	-	6V	40mA	
	KH-503	110VAC	6.3VAC	1.0W	-	-	ø30
	KH-503L		-	-	6V	40mA	
	KH-503TL	6.3V, 12V, 24V	6.3V, 12V, 24V	1.0W	-	-	
	KH-504	220VAC	6.3VAC	1.0W	-	-	
	KH-504L		-	-	6V	40mA	
	KH-505	380VAC	6.3VAC	1.0W	-	-	
	KH-505L		-	-	6V	40mA	
	KH-506	440VAC	6.3VAC	1.0W	-	-	
KH-506L	-		-	6V	40mA		
	KH-501DL KH-503DL	6VDC	-	-	6V	40mA	KH-501DL : ø25 KH-503DL : ø30
		12VDC	-	-	12V	20mA	
		24VDC	-	-	24V	20mA	
		48VDC	-	-			
		100VDC	-	-			
		125VDC	-	-			
		200VDC	-	-			
	KH-501-1	110VAC	6.3VAC	1.0W	-	-	ø25
	KH-50L-1		-	-	6V	40mA	
KH-501-1 KH-502-1	KH-501TL-1	6.3V, 12V, 24V	6.3V, 12V, 24V	1.0W	-	-	ø25
KH-503-1	KH-502-1	220VAC	6.3VAC	1.0W	-	-	ø25
	KH-502L-1		-	-	6V	40mA	

KH-504-1	KH-503-1	110VAC	6.3VAC	1.0W	-	-	ø30	
	KH-503L-1		-	-	6V	40mA		
	KH-503TL-1	6.3V, 12V, 24V	6.3V, 12V, 24V	1.0W	6V	6V:40mA 12V,24V:20mA		
	KH-504-1	220VAC	6.3VAC	1.0W	-	-		
	KH-504L-1		-	-	6V	40mA		
	KH-501DL-1 KH-503DL-1	6VDC	-	-	6V	40mA		KH-501DL-1 : ø25 KH-503DL-1 : ø30
		12VDC	-	-	12V	20mA		
		24VDC	-	-	24V	20mA		
		48VDC	-	-				
		100VDC	-	-				
125VDC		-	-					
200VDC	-	-						
KH-508-1 KH-508L-1 KH-508-2 KH-508L-2 KH-508-3 KH-508L-3 KH-508-4 KH-508L-4 KH-508-TL KH-508DL	KH-508-1	110VAC	6.3VAC	1.0W	-	-	ø30	
	KH-508L-1		-	-	6V	40mA		
	KH-508-2	220VAC	6.3VAC	1.0W	-	-		
	KH-508L-2		-	-	6V	40mA		
	KH-508-3	380VAC	6.3VAC	1.0W	-	-		
	KH-508L-3		-	-	6V	40mA		
	KH-508-4	440VAC	6.3VAC	1.0W	-	-		
	KH-508L-4		-	-	6V	40mA		
	KH-508-TL	6.3V, 12V, 24V	6.3V, 12V, 24V	1.0W	-	-		
	KH-508DL	6VDC	-	-	6V	40mA		
		12VDC	-	-	12V	20mA		
		24VDC	-	-	24V	20mA		
		48VDC	-	-				
		100VDC	-	-				
125VDC		-	-					
200VDC	-	-						

SPECIFICATIONS

Ambient Temperature	-25°C ~ +40°C(under unfrozen condition)
Ambient Humidity	45 ~ 85%RH
Insulation Resistance	50M Ohms min. at 500VDC
Rated Insulation Voltage	600V
Thermal Rated Current	6A max.
Contact Resistance	50mOhms max.(initial value)
Dielectric Strength	1,500VAC(50 /60Hz) for 1min.
Vibration	10 ~ 55Hz, double amplitude 1.5mm(X,Y,Z direction)
Shock	Approx. 50G(500m/s ²)
Protection	IP 50 (*KH-501-1, 502-1, 503-1, 504-1, 508 : IP 40)
Service Life	Lamp Type: 1,000 hours, LED Type: Semi-permanent
Material	Body : ABS Resin Lamp Cap : AS Resin Ring : ABS Resin(Cr plating)
Weight(Approx.)	KH-501 ~ 506 : Approx. 105g, KH-501TL, 503TL : Approx. 41g KH-501-1 ~ 504-1 : Approx. 126g, KH-501TL-1, 503TL-1 : Approx. 42g KH-508 : Approx. 163g, KH-508TL : Approx. 102g