

DIGITAL SOUND LEVEL METER WITH TEMPERATURE & HUMIDITY MS6702

Features:

- ▶ Sound Level Range: 30dB~130dB
- ▶ Large Digital LCD Display with Bar Graph
- ▶ Ambient Temperature and Relative Humidity Measurement
- ▶ Fast/Slow Selection
- ▶ Weighting A/C Selection
- ▶ Date and Time Display
- ▶ AC/DC Auxiliary Output
- ▶ Back Light and Auto Power Off

Specifications

MS6702

Specifications	Range
Measurement Range	30dB~130dB
Accuracy	±2dB
Resolution	0.1dB
Display	2000 counts
Sample Rate	2 times/s
Frequency Range	30Hz~8KHz
Over Range Indication	"UNDER" / "OVER"
Auxiliary Output	AC: 0.707 Vrms At Full Range For Each Level Impedance 600Ω DC: 10mV/dB, impedance 100Ω
Temperature	-20°C~10°C ±1°C 10°C~60°C ±2°C
Relative Humidity	10%~90% ±3.5%RH
Analog Bar Indication	●
Auto range & Manual range	●
Auto power off	●
Fast/Slow selection	●
°C/°F Selection	●
MAX value hold function	●
A/C weighting selection	●
Display Backlight	●
Low Battery display	●
General	
Power Supply	6x1.5V AAA Batteries
Product Size	265mm×80mm×69mm/ 10.4"×3.15"×2.7"
Product Weight	317g/0.7lb



MS6702

RANGE
30dB~130dB

FREQUENCY
30Hz~8KHz

